

# 500 500

## **FEATURES**

- Measures blood pressure/pulse rate and weight
- Interactive 10.4" touchscreen display
- Educational resource screens
- Color coded results chart
- Blood pressure guidelines display
- Save and track user biometrics
- Body Mass Index (BMI) Calculator
- Internet ready
- IR and USB data ports
- Proven accuracy meets AAMI standards
- Special options available (see back)
- Bilingual: English/Spanish

### **BENEFITS**

- Promotes wellness, health and safety for users, thus reducing healthcare costs
- Provides a snapshot of current health data and allows monitoring
- Helps employers measure and monitor work force health status
- Provides important data that can help build result-oriented health promotion programs
- Engage both employers and employees in the health management process for lowering and/or eliminating health risks

# SPECIFICATIONS



**INFLATION CUFF** 



**LCD DISPLAY** 



OPTIONAL CONFIGURATION

Custom Inserts Available

#### **Equipment**

Class II medical device manufactured in Merge's FDAregulated, ISO 13485 certified facility

#### **Accuracy**

Complies with AAMI (Association for the Advancement of Medical Instrumentation) Standards +/- 5 mmHg (millimeters of mercury)

#### **Rate of Cuff Inflation**

· Approximately 8 mmHg/sec

#### **Temperature**

Operating: 50 to 104° F (10 to 40° C)

**Storage:** -40 to 131° F (-40 to 55° C)

#### **Humidity**

Operating: 10 to 95% (non-condensing)
Storage: 10 to 95% (non-condensing)

#### **Weight Measurement**

Range: 40 to 440 lbs Accuracy: +/- 1 lb

#### **Measurement Range**

Systolic: +50 to +260 mmHg Diastolic: +30 to +240 mmHg

Pulse: 40 to 199 bpm

#### **Measurement Method**

Oscillometric

#### **Overpressure Limit**

· 310 +/- 10 mmHg

#### **Test Time**

· Typically less than one minute

#### **Physical Dimensions**

Height: 68.0in (170.0cm)
Width: 33.5in (85cm)
Depth: 25.0in (63.5cm)

#### Weight

Model LC-500: 175 lbs (79.3kg)

(standard cabinet)
· 200 lbs (90.7kg)
(wheelchair accessible cabinet)

#### **Input Power**

- · 117 VAC, 60Hz
- Power Supply Switch Selectable: 120/240 VAC, 50-60Hz)
- · 2.5 Amps
- · 3-Wire Grounded Outlet

#### **Blood Oxygen Measurement**

Method: Infrared Accuracy: +/- 2%

#### **Special Options**

- · Blood Oxygen Saturation,
- · 2.25" Printer
- Magnetic Stripe Reader
- · Wheelchair Accessibility

Data ports allow for downloading glucose meters, pedometers, etc.

